

CUBISCAN 150

STATIONARY DIMENSIONING FOR LARGE PARCELS



USER BENEFITS

- Quick, reliable dimensions on inbound & outbound shipments
- Simple and fast package processing
- Reduce shipping costs by eliminating unnecessary fees and penalties

PARCEL TYPES

- Cuboidal

PRODUCT DESCRIPTION

Handle large parcels with ease using the versatile Cubiscan® 150. This robust system accurately measures dimensions and weight for efficient large parcel manifesting and shipping. It optimizes warehouse workflows by providing instant dimensional data for storage location selection, cartonization, and facility layout. With the user-friendly visual display, you can view dimensions, weight, and even see calculations for dimensional weight for immediate strategic decision-making. Improve margins and efficiency across your entire operation with the Cubiscan 150.

- Equipped with the largest measurement range and weight capacity of Cubiscan's small, stationary dimensioning systems
- Roller ball table allows for easy package pass through
- Complete mobility means easy access and use anywhere in your warehouse
- Compatible with case packing/load optimization software packages
- Eliminates manual data entry and protects data integrity





PRODUCT FEATURE

- Ultrasonic sensing technology
- One-touch measuring & weighing
- Integrated digital display & controlpanel
- User-friendly roller ball table
- Large platform for large-capacity measurements

CUBISCAN 150 PERFORMANCE SPECIFICATIONS

Measurement Capacities	Minimum	Maximum
Length	8 cm	120 cm
Width	6 cm	99 cm
Height	6 cm	101 cm
Weight	0.02 kg	70 kg

Operating speed: 1-2 seconds
Dimensional increment: 0.5 cm

Weight increment: 0.02 kg
Table Height: Adjustable between 71-97 cm

PHYSICAL SPECS

Length: 165 cm
Width: 132 cm
Height: 221 cm
Weight: 195 kg

ENVIRONMENTAL

Operating temperature: -10° to 40°C
Humidity: 0% to 90% non-condensing

MEASUREMENT SENSOR

Four Load Cells
Ultrasonic

DATA OUTPUT AND POWER REQUIREMENTS

Power requirements: 100-240 VAC, 47-63 Hz, 0.15A
Data outputs: Ethernet (1), Serial (2), USB-A (1), USB-B (1)

